



Dedicated portable microbiology kits

AQUASAFE® MSL50

This dedicated microbiological kit allows easy and portable incubation of your samples through a dual incubator unit. Two efficient independently controlled chambers allow discrete testing of 2 organisms, for example faecal (thermotolerant) and total coliforms, simultaneously.

- IP68 waterproof buoyant carry case
- High performance removable and rechargeable power pack integrated into the case
- Docking station technology allows switching between in-case and bench top operation quickly and easily
- Lightweight dual incubator incorporating PetriLok® technology to ensure complete sample stability
- Wheeled case with retractable handle allows for simple portability in any situation with the minimum of user fatigue
- Dedicated engineered storage tray ensures all consumables and accessories are organised and kept in good condition within the kit



DESCRIPTION	PRODUCT CODE
MSL50	WT10-500

AQUASAFE® MSL25

A compact yet rugged simple kit dedicated to microbiological testing in the field. The single chamber dockable incubator fits into the small case, along with all the necessary accessories and consumables, using a specially designed storage tray. This keeps them safe from damage or loss.

- IP68 waterproof buoyant carry case
- High performance removable and rechargeable power pack integrated into the case
- Docking station technology allows switching between in-case and bench top operation quickly and easily
- Lightweight single incubator incorporating PetriLok® technology to ensure complete sample stability
- Compact case with shoulder strap provides a simple and effortless portable solution
- Dedicated engineered storage tray ensures all consumables and accessories are organised and kept in good condition within the kit



DESCRIPTION	PRODUCT CODE
MSL25	WT10-600

TECHNICAL SPECIFICATIONS

Test programs	<ul style="list-style-type: none"> • 37°C, 44°C, user defined (20°C to 50°C). • Adjustable 24 hour countdown timer.
Timer	<ul style="list-style-type: none"> • Adjustable • 24 hours with built in 'pause on power loss' feature
No of incubation chambers	• 2 Aquasafe MSL50 / 1 Aquasafe MSL25
Max petri dish capacity	• 50 Aquasafe MSL50 / 25 Aquasafe MSL25
Temperature Range (incubator)	• 20°C to 50°C
Temperature Resolution	• 0.1°C
Temperature Stability	• +/- 0.1°C
Dimensions mm	• 430 x 290 x 280
Weight Kg	• 20 Aquasafe MSL50 / 12 Aquasafe MSL25
Approvals	• IP68, CE-conformity
Features of the case and its components	<ul style="list-style-type: none"> • Fully waterproof and buoyant with both handle and shoulder strap • Case floats, even when full • In-Case docking station technology • Specifically designed and engineered storage tray as standard for consumables and accessories • PetriLok® technology on every petri-dish stack

For a full range of consumables- see pages 64- 68.

